

TWIN-20 DOUBLE PUMPS TEMPORIZED/VOLUMETRIC DOSING

Cod. 860016



by seko

TWINDOSE 20 dispenser was designed to dispense chemicals to door and conveyor-type ware-washing machines by using an advanced technology to meter precise amounts of product.

FEATURES:

- **Selectable power supply** 24 - 115 - 230 Vac 50/60 Hz
- **IP65** Protection degree and **class II** electrical insulation
- **Separate Level Control Inputs** for detergent and rinse aid pump.
- **Analogic Speed Control (15-100%)** of **Det and Rinse Aid pump on rinse signal** via potentiometer on the board. **Analogic Time control** (0-200 sec) of **Det dosing on 1st charge signal** via potentiometer.
- **Manual Priming** of the pumps via external buttons on the front cover
- Suitable for machines with 1 or 2 Solenoid Valves.



TECHNICAL FEATURES

Code	860016
Certification	CE, EAC
Interface	Analogic with LED display
Protection Degree	IP65
Electrical Class	Class II (ground connection not needed)
Power Supply	24 – 115 - 230 Vac
Consumption	8 W
Case Material	ABS
Dimensions	L. 195 – H. 168 – D. 110

HYDRAULIC PERFORMANCE DATA

Detergent Pump Flow Rates	1...6 l/h*
Rinse Pump Flow Rates	0,18...1,0 l/h*
Rinse Max Working Backpressure	3 bar
Detergent Peristaltic Tube	Santoprene (6x10)
Rinse/Sanitizer Peristaltic Tube	Sekobrill (3x8)
Lifetime of Squeeze Tubings	> 500 working hours*
External Tube Fitting	4 x 6 mm with nuts